



OFFICIAL LISTING

NSF certifies that the products appearing on this Listing conform to the requirements of
NSF/ANSI/CAN 61 - Drinking Water System Components - Health Effects

This is the Official Listing recorded on March 12, 2025.

MANN+HUMMEL Water & Fluid Solutions, Inc.
93 South La Patera Lane
Goleta, CA 93117
805-964-8003

Facility: Goleta, CA

Mechanical Devices

Trade Name	Size	Water Contact Temp	Water Contact Material
Reverse Osmosis Element			
4040-ACM2-TSFN ^[1]	4" x 40"	CLD 23	MLTPL
4040-ACM2-TWFN ^[1]	4" x 40"	CLD 23	MLTPL
4040-ACM4-TSFN ^[1]	4" x 40"	CLD 23	MLTPL
4040-ACM4-TWFN ^[1]	4" x 40"	CLD 23	MLTPL
4040-ACM5-TSFN ^[1]	4" x 40"	CLD 23	MLTPL
4040-ACM5-TWFN ^[1]	4" x 40"	CLD 23	MLTPL
8040-ACM2-TSAN ^[1]	8" x 40"	CLD 23	MLTPL
8040-ACM2-TSFN ^[1]	8" x 40"	CLD 23	MLTPL
8040-ACM2-UWAN ^[1]	8" x 40"	CLD 23	MLTPL
8040-ACM2-UWFN ^[1]	8" x 40"	CLD 23	MLTPL
8040-ACM3-TSAN ^[1]	8" x 40"	CLD 23	MLTPL
8040-ACM3-TSFN ^[1]	8" x 40"	CLD 23	MLTPL
8040-ACM3-UWAN ^[1]	8" x 40"	CLD 23	MLTPL
8040-ACM3-UWFN ^[1]	8" x 40"	CLD 23	MLTPL
8040-ACM4-TSAN ^[1]	8" x 40"	CLD 23	MLTPL
8040-ACM4-TSFN ^[1]	8" x 40"	CLD 23	MLTPL
8040-ACM4-UWAN ^[1]	8" x 40"	CLD 23	MLTPL
8040-ACM4-UWFN ^[1]	8" x 40"	CLD 23	MLTPL
8040-ACM5-TSAN ^[1]	8" x 40"	CLD 23	MLTPL
8040-ACM5-TSFN ^[1]	8" x 40"	CLD 23	MLTPL
8040-ACM5-UWAN ^[1]	8" x 40"	CLD 23	MLTPL
8040-ACM5-UWFN ^[1]	8" x 40"	CLD 23	MLTPL
8540-ACM2-TSFN ^[1]	8.5" x 40"	CLD 23	MLTPL
8540-ACM2-UWFN ^[1]	8.5" x 40"	CLD 23	MLTPL
8540-ACM4-TSFN ^[1]	8.5" x 40"	CLD 23	MLTPL
8540-ACM4-UWFN ^[1]	8.5" x 40"	CLD 23	MLTPL
8540-ACM5-TSFN ^[1]	8.5" x 40"	CLD 23	MLTPL
8540-ACM5-UWFN ^[1]	8.5" x 40"	CLD 23	MLTPL
MICRODYN RO 4040-BW ^[1]	4" x 40"	CLD 23	MLTPL
MICRODYN RO 4040-LE ^[1]	4" x 40"	CLD 23	MLTPL
MICRODYN RO 4040-TW ^[1]	4" x 40"	CLD 23	MLTPL
MICRODYN RO 8040-BW-365 ^[1]	8" x 40"	CLD 23	MLTPL

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



MICRODYN RO 8040-BW-400 ^[1]	8" x 40"	CLD 23	MLTPL
MICRODYN RO 8040-BW-400/34 ^[1]	8" x 40"	CLD 23	MLTPL
MICRODYN RO 8040-BW-440 ^[1]	8" x 40"	CLD 23	MLTPL
MICRODYN RO 8040-LE-400 ^[1]	8" x 40"	CLD 23	MLTPL
MICRODYN RO 8040-LE-400/34 ^[1]	8" x 40"	CLD 23	MLTPL
MICRODYN RO 8040-LE-440 ^[1]	8" x 40"	CLD 23	MLTPL
TRISEP® 8040-SB20-TSFA ^[1]	8" x 40"	CLD 23	MLTPL
TRISEP® 8040-SB50-TSFA ^[1]	8" x 40"	CLD 23	MLTPL
TRISEP® 8040-SB90-TSFA ^[1]	8" x 40"	CLD 23	MLTPL
TurboClean® Bev 8040-NF-CA ^[2]	7.9" x 40"	CLD 23	MLTPL
TurboClean® Bev 8040-NF-CA-0 ^[2]	7.9" x 40"	CLD 23	MLTPL
TurboClean® Bev 8040-RO-CA ^[2]	7.9" x 40"	CLD 23	MLTPL
TurboClean® Bev 8040-RO-CA-0 ^[2]	7.9" x 40"	CLD 23	MLTPL
TurboClean® Bev 8340-NF-CA-0 ^[2]	8.3" x 40"	CLD 23	MLTPL
TurboClean® Bev 8340-RO-CA-0 ^[2]	8.3" x 40"	CLD 23	MLTPL

[1] The 4040 models are certified for a minimum flow of 250 gallons per day. The 8040 models are certified for a minimum flow of 1100 gallons per day. The 8540 models are certified for a minimum flow of 1300 gallons per day. Product requires a 1 hour conditioning flush with potable water prior to use.

[2] Certified for a minimum daily flow of 2,800 gallons per day.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.